

Relion Battery Specs:

**RB-52 LT: (LiFePo4 Battery 12V 52Ah Group 31 case with auto heating)**

Dimensions- 7.8"x6.5"x6.8"

Weight: 14.1lbs

Terminal Type: M8

Waterproof Rating : IP67

High impact case: ABS & Polycarbonate blend

Flame retardant case: UL-94-V0 flame rating

Cell type-Chemistry: Cylindrical – LiFePO4

Certifications: UN38.3, UKCA & CE (battery) UL1642 (cells) (File# MH64523) IEC62133 (cells)

Warranty: 10 Years free shipping each way due to their shipping classification UN 3480 Class 9

Warranty Specifics: Years 1-3 (full replacement free of charge); Years 4-5 (similar product will be offered at 20% off retail) and Years 6-10 (similar product will be offered at 10% off retail)

LT series: low temperature charging, fully automatic (1 hour @ 4Amps)

(Battery charge temps are -4 to 113 Degree F)

Customer support: Technical support hot line (8am to 8pm EST)

Shipping: Free shipping on orders over 10K

**RB-100 LT: (LiFePo4 Battery 12V 100Ah Group 31 case with auto heating)**

Dimensions- 13"x6.8"x8.4"

Weight: 27.9lbs

Terminal Type: M8

Waterproof Rating : IP67

High impact case: ABS & Polycarbonate blend

Flame retardant case: UL-94-V0 flame rating

Cell type-Chemistry: Cylindrical – LiFePO4

Battery comes with a rope handle for transportation

Certifications: UN38.3, UKCA & CE (battery) UL1642 (cells) (File# MH64523) IEC62133 (cells)

Warranty: 10 Years free shipping each way due to their shipping classification UN 3480 Class 9

Warranty Specifics: Years 1-3 (full replacement free of charge); Years 4-5 (similar product will be offered at 20% off retail) and Years 6-10 (similar product will be offered at 10% off retail)

LT series: low temperature charging, fully automatic (1 hour @ 10Amps)

(Battery charge temps are -4 to 113 Degree F)

Customer support: Technical support hot line (8am to 8pm EST)

Shipping: Free shipping on orders over 10K

**RB-300 LT: (LiFePo4 Battery 12V 300Ah Group 31 case with auto heating)**

Dimensions- 20.6"x10.5"x8.7"

Weight: 76.1lbs

Terminal Type: M8

Waterproof Rating : IP67

High impact case: ABS & Polycarbonate blend

Flame retardant case: UL-94-V0 flame rating

Cell type-Chemistry: Cylindrical – LiFePO4

Battery comes with a rope handle for transportation

Certifications: UN38.3, UKCA & CE (battery) UL1642 (cells) (File# MH64523) IEC62133 (cells)

Warranty: 10 Years free shipping each way due to their shipping classification UN 3480 Class 9

Warranty Specifics: Years 1-3 (full replacement free of charge); Years 4-5 (similar product will be offered at 20% off retail) and Years 6-10 (similar product will be offered at 10% off retail)

LT series: low temperature charging, fully automatic (1.5 hour @ 15 Amps)

(Battery charge temps are -4 to 113 Degree F)

Customer support: Technical support hot line (8am to 8pm EST)

Shipping: Free shipping on orders over 10K