| REVISIONS | | | | |
|---|---|---|---|---|
| ZONE | REV | DESCRIPTION | DATE | APPROVED |
| | A | INITIAL RELEASE<br>ECP 1062<br>ECO A10136 (NA) | 230816 | S. HAYES |

CAD MAINTAINED. CHANGES SHALL BE INCORPORATED BY THE DESIGN ACTIVITY.

NOTES - UNLESS OTHERWISE SPECIFIED:

1. MATERIAL: WAVEGUIDE PER MIL-W-85, FLANGES PER MIL-F-3922
2. WORKMANSHIP PER MIL-HDBK-454 GUIDELINE 9.
3. FINISH:
   3.1. CHEMICAL FILM TREATMENT PER MIL-C-5541, CLASS 3.
   3.2. PAINT PER AMS-STD-595, COLOR 17925, SEMI GLOSS.
   3.3. PRIMER PER MIL-DTL-53022CL, 2 COATS. TOP COAT PER MIL-PRF-22750, 2 COATS.
   3.4. OMIT PAINT FROM ALL HOLES, FLANGE FACES (MATING SURFACES) AND INTERNAL SURFACES.
4. BRAZE PER MIL-HDBK-454 GUIDELINE 59, QUALITY PER MIL-B-7883, GRADE B. ALTERNATIVELY, WELDS PER MIL-HDBK-454 GUIDELINE 13.
5. FLANGES SHALL BE SQUARE TO THE INNER SURFACE OF THE WAVEGUIDE TO WITHIN .005".
6. UNIT WITH END SEALS MUST WITHSTAND MAXIMUM DROP IN AIR PRESSURE OF 1 PSI PER 6 HOURS LEAKAGE FROM AN INITIAL PRESSURE OF 8 PSIG AFTER REMOVAL OF SOURCE OF AIR PRESSURE.
7. THE PART NUMBER IS THE DRAWING NUMBER SUFFIXED WITH THE APPLICABLE DASH NUMBER AS SHOWN IN TABLE A.
8. SHIPPING CAPS TO BE FURNISHED WITH WAVEGUIDE ASSEMBLY.
9. ELECTRICAL CHARACTERISTICS:
   9.1. FREQUENCY: 2.7 TO 3.0 GHZ
   9.2. VSWR: 1.10 MAX
   9.3. INSERTION LOSS: 0.10 DB MAX
10. POWER REQUIREMENTS:
   10.1. 1.1 MW PEAK POWER BETWEEN 2.7 TO 3.0 GHZ AT 0 PSIG AND DRY AIR, NO ARCING PERMITTED.
   10.2. 2.2 KW AVERAGE POWER WITH MAXIMUM DUTY CYCLE OF 0.2% BETWEEN 2.7 AND 3.0 GHZ, 0 PSIG AND DRY AIR, NO ARCING PERMITTED.
11. SUGGESTED SOURCE(S) OF SUPPLY (MANUFACTURER(S)):
    VENDOR: TBD (CAGE CODE TBD)
    VENDOR CITY: TBD




TABLE A

| DASH NO. | APPLICABLE INFORMATION |
|---|---|
| 201 | SHEET 1 |

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

VENDOR ITEM CONTROL DRAWING

| | | | |
|---|---|---|---|
| MATERIAL | | INTERPRET DRAWING IAW ASME Y14.100 | PROJECT: WSR-88D |
| | | INTERPRET DIMENSIONS AND TOLERANCES IAW ANSI Y14.5M | APPROVALS / DATE |
| | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: MILLIMETERS X PL ±.25 / DECIMALS X PL ±.010 / X PL ±.010 | DWN C. STILLWELL 230816 |
| | | | CHK J. MORAN 230816 |
| | | | ENGR S. HAYES 230816 |
| | | | QA |
| | | | LOG L. ALBERTS 230816 |
| THIRD ANGLE PROJECTION | | ANGLES ±0° DO NOT SCALE DRAWING | DOC M. KARBOWSKI 230816 |
| | 230141 NEXRAD | ECP 1062 | CM |
| | NEXT ASSY USED ON | | ROC |
| | APPLICATION | | |

88D/RSB/307
WSR-88D RADAR OPERATIONS CENTER
1313 HALLEY CIRCLE
NORMAN, OKLAHOMA 73069-8480

WAVEGUIDE ASSEMBLY, RF PALLET, S BEND, 12.1 X 7.6 INCH

| SIZE | CAGE CODE | DWG NO. | REV |
|---|---|---|---|
| E | 0WY55 | 2200688 | A |

SCALE 1/1 SHEET 1 OF 1

CM FORM 2990008

# 2200688-201

**Revision** • A A10136
**Part** • WAVEGUIDE ASSEMBLY, RF PALLET, DUAL E-BEND, 12.1 X 7.6 INCH ( 2A5WG1, 2A5WG7 ) •
Effective From: **08/15/2023 10:00:00 PM PDT** to
**...**

# Production

Unincorporated

## Title Block

| | |
|---|---|
| **Lifecycle Phase:** | Production |
| **Nomenclature:** | WAVEGUIDE ASSEMBLY, RF PALLET, DUAL E-BEND, 12.1 X 7.6 INCH ( 2A5WG1, 2A5WG7 ) |
| **Size:** | J |
| **Part Type:** | Part |
| **Rev Release Date:** | 08/24/2023 08:26:07 AM PDT |
| **Effectivity Date:** | 08/15/2023 10:00:00 PM PDT |
| **Base Model:** | |
| **Number:** | 2200688-201 |
| **Rev:** | A A10136 |
| **Product Line(s):** | OSF |
| **Part Category:** | Vendor Item Control Document |
| **Rev Incorp Date:** | |

## MFG Info

| | |
|---|---|
| **CAGE CODE:** | 0WY55 |
| **DESCRIPTION:** | |
| **MFR 1 CAGE:** | 6X307 |
| **MANUFACTURER 2:** | |
| **MFR 2 PART NO.:** | |
| **MFR 3 CAGE:** | |
| **UOM:** | EACH |
| **CABLE LENGTH:** | |
| **CABLE MARKER - TO:** | |
| **DRAWING NO.:** | 2200688 |
| **MANUFACTURER 1:** | FERRITE CO. |
| **MFR 1 PART NO.:** | SWG-39-4-0 |
| **MFR 2 CAGE:** | |
| **MANUFACTURER 3:** | |
| **MFR 3 PART NO.:** | |
| **EAR:** | |
| **CABLE MARKER - FROM:** | |
| **NOTES:** | |