Truck Lift Fork RCD 180/900 or equivalent FFP
Description of Requirement: STILL RCD 180/900 Truck Lift Fork or Equal

Type
Basic Truck: Diesel forklift Truck type RCD 180/900 or EQUAL
Drive Unit: Mercedes Benz OM934 engine EU5
Min 149 kW Max 151kW;
Front Tires: twin Super elastic, SIT system, 12.00-24 heavy duty
Rear Tires: single Super elastic, SIT system, 12.00-24/8.5 heavy duty;

Mast
Mast: clear-view mast with free lift;
Closed height: Min 3,480 mm to Max 3,490 mm;
Rated lift: Min 3,495 mm to Max 3,502 mm;
Free lift: Min 145 mm to Max 155 mm;
Maximum height: Min 5,155 mm to 5,161 mm;
Basic load-carrying capacity: Min 16,999 kg to Max 18,001 kg;
Basic capacity to lift height: Min 4,880 mm to Max 4,895 mm;
Load Center of gravity: The load center of gravity for this truck is 900 mm;
Maximum width: Min 1,290 mm to Max 1,295 mm;
Fork carriage: Length 2,400 mm, Cross section 250x100 mm,
Extra Hydraulic coupling: Push-in coupling 3. and 4.;

Cabin area
Overhead guard: Enclosed cabin with tinted windows, tinted panoramic safety glass roof.
Heated rear window
Driver's seat: Deluxe, height-adjustable, air-suspended, heated, fabric;
Heating/air conditioning: Automatic climate control, temperature selector switch, fan speed selector switch, selector switch for ventilation nozzles, anti-pollen filter, three fans in cabin roof
Sun visor front and roof window;
Hydraulic controls: Joystick 4-Plus

Specification
Lighting system LED version front: 2 LED headlights with drive direction indicators rear: LED tail and brake lights, drive direction indicators, warning lights (including mini-console);
Activation lighting system: Via switch working spotlight rear: LED version, on overhead guard, top, right;
Working spotlight front: LED version, on overhead guard, top, left and right; Activation WS front: Via switch Warning light: Flashing beacon beneath roof; Activation warning light: Via switch;
Color code: Orange/silver metallic (lead/cadmium free);
Labelling: German;
Documentation: 1 x operating and maintenance manual 1 x spare parts list;
Fuel system: Diesel fuel tank 58 liters;
Air filter system: Dry air filter, with maintenance indicator in display;
Cooling system: Coarse mesh radiator

Delivery
LRC, RSSA
Building 113
Rose Barracks
Vilseck, 92249
Germany

Warranty: Standard warranty provided by vendor. Specify on quote.