SPECIAL PACKAGING INSTRUCTION

CODE ID	SPI NO (TPO)
98752	FND165348L
	SHEET 1 OF 2

PART OR DRAWING NO.	NATIONAL STOCK NO.	CURR REV
60244-45100-10	5895-ND-165-348L	

ITEM NOMENCLATURE
POWER CONTROL UNIT, A1

ORIG DATE
23263

ILL	D. THORNTON
PS	L. MARTINEZ
CHK	J. KERR
AUTH	C. WILLIAMS

PRESERVATION: IAW MIL-STD-2073-1
SERVICEABLE METHOD: 10
UNSERVICEABLE METHOD: 10

QUP: 001

ICQ: 000

CLEANING & DRYING: IAW MIL-STD-2073-1

PRESERVATIVE: NA

MARKING: IAW MIL-STD-129

SPECIAL MARKINGS:
A) SPI NO. FND165348L
B) REUSABLE CONTAINER AND DUNNAGE, DO NOT DESTROY
C) NOT FOR OUTSIDE STORAGE

CLOSURE:
LEVEL A: IAW ASTM D 6251
LEVEL B: IAW ASTM D 6251

PACKING: AS SPECIFIED BELOW AND BILL OF MATERIALS

LEVEL	SPEC	STYLE	TYPE	CL	VRTY	GR	TR
A	ASTM D 6251	A	III	2			SEE NOTE 1
B	ASTM D 6251	A	III	2			

	LEVEL A	LEVEL B
GROSS CU FT	21.90	21.90
GROSS WT LBS	160	
DESIGN FRAGILITY G	110	

	LENGTH	WIDTH	DEPTH
CNTNR I.D.			
LEVEL A	52 3/4	25	20
LEVEL B	52 3/4	25	20
CNTNR O.D.			
LEVEL A	55	27 1/4	25 1/4
LEVEL B	55	27 1/4	25 1/4
ITEM DIM:	40 3/4	13	8

ITEM WT LBS: 100

REVISIONS		
LTR	DESCRIPTION	DATE

NOTICE: SEE SPIRES FOR A COMPLETE LISTING OF NSN'S ASSIGNED TO THIS SPI.

NOTES:

1. ALL WOODEN LUMBER, WOODEN PALLETS, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO HEAT TREATED (HT) MATERIAL (HT 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES (LATEST REVISION OF ISPM NO.15) AND DOD 4140.01-M-1 COMPLIANCE FOR DEFENSE PACKAGING: PHYTOSANITARY REQUIREMENTS FOR WOOD PACKAGING MATERIAL (WPM) OFFICE. THIS INFORMATION CAN BE FOUND AT WWW.IPPC.INT.
2. FILL ANY VOIDS WITH CUSHIONING TO PREVENT MOVEMENT.

SPI NO. FND165348L

SPECIAL PACKAGING INSTRUCTION

CODE ID
98752

SPI NO. (TPO)
FND165348L

ITEM NOMENCLATURE
MAIN CONTROL UNIT

4	2	TOP AND BOT CUSHIONING	24 X 25 X 6	A-A-59136
3	2	SIDE CUSHIONING	24 X 9 X 6	A-A-59136
2	2	END CUSHIONING	25 X 21 X 6	A-A-59136
1	1	CONTAINER		SEE PACKING
PART NO.	QTY	NOMENCLATURE OR DESCRIPTION	SIZE (INCHES UNLESS SPECIFIED) TOLERANCES ON FRAC ± 1/8, DECIMAL ± .01, ANGLES ± 1°	MATERIAL SPECIFICATION

SPI NO. FND165348L

COMPUTER GENERATED