AMENDED DESCRIPTION OF REQUIREMENT – SUPPLIES

4-Door UTV

The Grayling Air Gunnery Range, located in Northern Michigan, experiences extreme and highly variable weather conditions, including heavy lake-effect snow, which regularly results in accumulations of several feet. The operational area of the range encompasses a diverse and rugged landscape, including paved roads, unimproved trails, open ground, and densely wooded areas.

To ensure uninterrupted, year-round operational support, range personnel require a vehicle capable of safely and reliably transporting up to six personnel and their associated equipment across this challenging terrain in all weather conditions. This vehicle is essential for conducting range inspections, target maintenance, safety oversight, and emergency response.

2.0 Requirement

The Grayling Air Gunnery Range requires two (2) new, Can-Am Defender MAX Limited HD11, all-weather, all-terrain Utility Task Vehicle (UTV) complete with the following specified accessories and characteristics.

3.0 Required Specifications and Accessories

The vehicle must be a new Can-Am Defender MAX Limited HD11 in a **camouflage pattern**, and must include, at a minimum, the following factory-installed or dealer-installed items:

Engine: 999cc, 100 HP Rotax V-twin engine.

Cabin: Fully enclosed cab with heating, venting, and air conditioning (HVAC) climate system and full hard doors with electric-opening tinted windows.

Windshield: Glass, full-tilt front windshield with a wiper and washer kit.

Display: 10.25 in. touchscreen display with integrated rear-facing camera.

Mobility:

Can-Am branded all-season Apache 360 LT Track System.

A standard set of 30-in, 8-ply rated tires on 15-in cast-aluminum wheels.

Lighting: Roof-mounted LED light kit.

Storage & Racks:

Roof-mounted luggage rack.

Rear backrest storage.

~~Cargo bed extension carrier.~~

Foldable Tailgate Extension

Tailgate Panel Kit (Standard on item)

Protection

Front grille guard.

Front and rear bumpers.

Front and rear suspension arm guards.

Full-length underbody skid plate.

Mud guards.

Winch: 4,500 lb winch with synthetic cable.

Accessories: All necessary wiring harnesses, switches, and interior dome lighting for installed components.

*****IF YOU REQUIRE A BRAND NAME ITEM, DESCRIBE THE BRAND NAME, THE REASON IT MUST BE BRAND NAME (SUCH AS INDUSTRY STANDARD, COMPATIBILITY WITH EXISTING EQUIMENT, OR USAF STANDARD FOR USE. IF USING USAF STANDARD, YOU MUST PROVIDE DOCUMENTATION SUPPORTING THE STANDARD (DAFI, ANGI, ETC.).***